

# YZ-H688

## 羟基丙烯酸树脂

### 特性

- 1、超快干
- 2、硬度佳
- 3、耐候性好

### 用途

应用于汽车修补超快干清漆。

### 性质

特性	数值	单位
组份	丙烯酸共聚物	
外观	清澈透明	
固体份	65±2	%
黏度	5000-7000	mPa.s/25℃
酸值	4-7	mgKOH/g
溶剂	XYL/BAC	
色号	≤1(Fe-Co)	
羟基含量	3.5(固体份)	%

### 储存说明

- 远离热及火源, 置于阴凉通风处, 容器保持紧密。
- 本产品自生产日起, 保质期限为 12 个月。

### 包装规格

200kg/桶

### 安全

本产品含溶剂, 必须做好防护措施, 小心操作, 避免接触皮肤与眼睛, 其它详细资料请参考物质安全说明书。

以上资料系经试验所得, 仅供参考, 不作任何保证之用。鉴于树脂功能的局限性及用户要求的多样性, 若使用公司产品, 使用前请按自身的要求严格试验树脂的适应性及最终产品的稳定性。

版本: 2021-12-03

# YZ-H688

## Hydroxyl Acrylic Resins

### Characteristics

---

- 1、 Excellent weatherability ;
- 2、 Fast drying and high hardness.

### Application

---

Applied to super quick drying varnish etc.

### Property

---

Characteristics	Numeric value	Unit
Component	Acrylic copolymer	
Appearance	Clear and bright	
Solid Content	65±2	%
Viscosity	5000-7000	mPa.s/25°C
Acid Value	4-7	mgKOH/g
Solvent	XYL/BAC	
Color	≤1(Fe-Co)	
OH Content	3.5	%

### Storability

---

- Keep away from fire source, placed in a cool ventilated place, keep container tightly.
- Shelf time:12 months.

### Packing

---

200Kg/Berrel

### Safety

---

This product contains solvent, Please be careful operation, avoid contacting with skin and eyes, other information please refer to the material safety instruction.

---

The above information is provided for reference only. If you use our products, please strictly verify according to your own requirements .

Version : 2021-12-03