

YZ-H737P

羟基丙烯酸树脂

特性

- 1、干速快
- 2、硬度高
- 3、鲜艳性佳
- 4、光泽高

用途

应用于汽车漆、摩托车漆、塑胶漆、工业漆等色漆及罩光清漆。

性质

特性	数值	单位
组份	丙烯酸共聚物	
外观	清澈透明粘稠液体	
固体份	70±2	%
黏度	10000-20000	mPa.s/25°C
酸值	8-12	mgKOH/g
溶剂	XYL	
色号	≤1(Fe-Co)	
羟基含量	3.0(固体份)	%

储存说明

- 远离热及火源, 置于阴凉通风处, 容器保持紧密。
- 本产品自生产日起, 保质期限为 12 个月。

包装规格

200kg/桶

安全

本产品含溶剂, 必须做好防护措施, 小心操作, 避免接触皮肤与眼睛, 其它详细资料请参考物质安全说明书。

以上资料系经试验所得, 仅供参考, 不作任何保证之用。鉴于树脂功能的局限性及用户要求的多样性, 若使用本公司产品, 使用前请按自身的要求严格试验树脂的适应性及最终产品的稳定性。

版本: 2021-12-03

YZ-H737P

Hydroxyl Acrylic Resins

Characteristics

- 1、 Fast drying;
- 2、 High hardness ;
- 3、 Good vividness;
- 4、 High gloss.

Application

Applied to Car paint, motorcycle paint, plastic paint, industrial paint and other color varnish.

Property

Characteristics	Numeric value	Unit
Component	Acrylic copolymer	
Appearance	Clear and viscous liquid	
Solid Content	70±2	%
Viscosity	10000-20000	mPa.s/25°C
Acid Value	8-12	mgKOH/g
Solvent	XYL	
Color	≤1(Fe-Co)	
OH Content	3.0	%

Storability

- Keep away from fire source, placed in a cool ventilated place, keep container tightly.
- Shelf time:12 months.

Packing

200Kg/Berrel

Safety

This product contains solvent, Please be careful operation, avoid contacting with skin and eyes, other information please refer to the material safety instruction.

The above information is provided for reference only. If you use our products, please strictly verify according to your own requirements .

Version : 2021-12-03