

L4500

触变树脂

特性

- 1、铝粉定向排列
- 2、防沉降性能

用途

可以用于大、中巴车、摩托车、汽车修补漆以及运输工具用金属底漆，塑胶、家具等铜、铝、珍珠漆。

性质

特性	数值	单位
组份	乙烯醋酸乙烯共聚溶液	
外观	乳白色液体	
固体份	6.5±0.5	%
溶剂	BAC/XYL/NBA	

储存说明

- 远离热及火源，置于阴凉通风处，容器保持紧密。
- 本产品自生产日起，保质期限为 12 个月。

包装规格

50Kg/桶或 180Kg/桶

安全

本产品含溶剂，必须做好防护措施，小心操作，避免接触皮肤与眼睛，其它详细资料请参考物质安全说明书。

以上资料系经试验所得，仅供参考，不作任何保证之用。鉴于树脂功能的局限性及用户要求的多样性，若使用本公司产品，使用前请按自身的要求严格试验树脂的适应性及最终产品的稳定性。

版本：2023-06-25

L4500

Thixotropic resin

Characteristics

- 1、 Good aluminium orientation
- 2、 Good dustproof properties

Application

Used for large and middle-sized buses,motorcycle,automobile refinish and metal basecoat of vehicle and copper,aluminum,pearl paint on plastic and furniture.

Property

Characteristics	Numeric value	Unit
Component	EVA resin solution	
Appearance	Milky liquid	
Solid Content	6.5±0.5	%
Solvent	BAC/XYL/NBA	

Storability

- Keep away from fire source, placed in a cool ventilated place, keep container tightly.
- Shelf time:12 months.

Packing

50Kg/Berrel and 180Kg/Berrel

Safety

This product contains solvent, Please be careful operation, avoid contacting with skin and eyes, other information please refer to the material safety instruction.

The above information is provided for reference only. If you use our products, please strictly verify according to your own requirements .

Version : 2023-06-25